



OPTIONS:
E = For High Voltage applications
O = No options. Plain self leads as shown.

ELECTRICAL PARAMETERS				NOMINAL LEAD DIAMETER
PREM P/N	Nominal DCR	INDUCTANCE	DC AMPS	
SPE-400	0.001 Ω	1.5 μH	12	0.064"
SPE-401	0.0025 Ω	2.0 μH	10	0.057"
SPE-402	0.003 Ω	3.0 μH	8.5	0.051"
SPE-403	0.004 Ω	3.5 μH	7.0	0.045"
SPE-404	0.006 Ω	4.2 μH	5.5	0.040"
SPE-405	0.011 Ω	10 μH	4.3	0.036"
SPE-406	0.0155 Ω	20 μH	4.3	0.036"
SPE-407	0.0225 Ω	28 μH	3.4	0.032"
SPE-408	0.031 Ω	34 μH	2.6	0.029"
SPE-409	0.045 Ω	50 μH	2.1	0.025"
SPE-410	0.066 Ω	100 μH	2.1	0.025"
SPE-411	0.0895 Ω	125 μH	1.7	0.023"
SPE-412	0.125 Ω	160 μH	1.35	0.020"
SPE-413	0.1955 Ω	250 μH	1.0	0.035"
SPE-414	0.2425 Ω	350 μH	1.0	0.035"
SPE-415	0.3645 Ω	500 μH	0.85	0.032"
SPE-416	0.4815 Ω	600 μH	0.67	0.030"
SPE-417	0.672 Ω	750 μH	0.53	0.025"
SPE-418	0.800 Ω	1000 μH	0.42	0.025"
SPE-419	0.001 Ω	0.9 μH	13.0	0.064"

DATE	ISS	REVISION	CHECKED

Mech - Elect SPE-400 Series

Notes

ALL DIMENSIONS FOR REFERENCE ONLY

[] = millimeters

PREM

MAGNETICS INCORPORATED
3521 N. CHAPEL HILL RD.
JOHNSBURG, IL 60051

Mech - Elect PREM
PART # SPE-400
THROUGH SPE-419

Approved: TJK

Scale: NONE

Date: 11/13/2015